

**Watkins 25 with ISOMAT SPAR RIGGING -
 Bill of Material original factory date: 7-30-1985 for
 standing rigging and 4-24-1984 for running rigging.**

QTY.	Description	Wire Size and Type	Fitting	Fitting	Overall Dimension	Cut Dimension
Standing Rigging						
1	Head Stay	3/16 1x19	Stemball	6/12/12	30' 3 3/4"	29' 4 1/8"
1	Back Stay	3/16 1x19	Stemball	6/12/12	32' 3 1/4"	31' 3 5/8"
2	Upper Side Stay	3/16 1x19	Stemball	6/12/12	29' 9 1/4"	28' 9 5/8"
2	Lower Side Stay	3/16 1x19	Stemball	6/12/12	16' 5 1/2"	15' 5 7/8"
Note: Overall dimension is for turnbuckles 2/3 open.						
Standing Rigging Options						
1	Split Backstay Upper	3/16 1x19	Stemball	6/12/12	25' 8 1/2"	24' 9 1/8"
2	Split Backstay Lower	3/16 1x19	Jaw	Jaw		6' 10"
1	Supply Splitter Plate					
1	Head Stay with Anchor Platform	3/16 1x19	Stemball	6/12/12	30' 2 1/4"	29' 2 5/8"
Note: Use all small cups.						
Running Rigging						
1	Main Halyard	5/16" X.L.S.	Eye w/5620 Shackle	B.E.		56'
1	Jib Sheet	5/16" X.L.S.	Eye w/721-2 Shackle	B.E.		59'
1	Main Sheet	3/8" X.L.S.	B.B.E.	B.B.E.		45'
1	Genoa Sheet	3/8" X.L.S.	B.B.E.	B.B.E.		45'
1	Topping Lift	1/4" X.L.S.	Eye -	B.E.		41'
1	Reef Line	1/4" X.L.S.	Eye -	B.E.		22'
Running Rigging Opions						
1	Main Halyard Led Aft	5/16" X.L.S.	Eye w/5620 Shackle	B.E.		66'
1	Jib Halyard Led Aft	5/16" X.L.S.	Eye w/721-2 Shackle	B.E.		68'
1	Spinacer Halyard Led Aft	5/16" X.L.S.	Eye w/721-2 Shackle	B.E.		68'

Copied from original factory documents by
 John D. Myers 8-13-03